

MATERIALS

Rafters/trusses

As per structural requirements. To comply with SANS 563 Softwood structural timber and engineer's specifications.

MONIER Roofing Undertile Membrane

MONIER Roofing undertile membrane Agrément approved certificate 2004/304.

Battens

To comply with SANS 653 Softwood battens and branding.

Batten nails

Non-corrodible nails 3,35mm Ø - long enough to penetrate the rafter to a depth of 55mm.

Tiles

To comply with SANS 542 for concrete roof tiles.

Fittings

To suit design criteria.

Tile nails

Non-corrodible clout nails, as supplied by MONIER Roofing - long enough to penetrate the batten to 2/3 of its depth.

Tile clips

Non-corrodible "Storm clip".

Flashings

Non-corrodible flashing materials should be used. To avoid the possibility of electrolytic corrosion, always ensure that flashings, which come into contact with one another, are compatible.

General

Roofing components such as roof windows, clear tiles, coverfill and pigments, are also supplied by MONIER Roofing.



CLEAR TILE

The Clear Tile has been designed as a cost-effective means of illuminating rooms and is easy to install. It is a profile that has been constructed out of extremely durable, highly transparent polycarbonate. The Clear Tile has the same dimensions as those of the standard profiles and is available in the Coverland profiles - Cupola, Double Roman and Taunus.

This product has been produced to withstand the harshest elements for a prolonged period of time, is resistant to ultraviolet rays and will provide many years of trouble-free illumination.

Installation

The Clear tile is easy to install as it simply takes the place of the existing concrete roof tile. Each tile is fitted with a securing device for proper installation.

