

OCCITANE

Embodying the character of French landscapes



THE OCCITANE RANGE



The Occitane clay roof tile is imported from France and is made of Limoux clay, which gives the tiles their legendary performance of mechanical strength and frost resistance. The structure of the lock guarantees that the tile fits perfectly and because it is treated with silicone, in the finishing process excellent watertightness is ensured.

Reliable, easy and economical to lay thanks to its large covering capacity of 10 tiles in a square meter. The Occitane clay roof tile also has a marked "gauge" look that transforms a roof into a unique charm. The tile has a large format and a range of divided gauges offering greater flexibility in laying.

Occitane clay tiles are available in a range of colours to fit in perfect harmony with the environment. Colours available are Silvacane Littoral, Silvacane Xahara and Red. These colours bring the patina of age onto a roof, while following up to date roofing solutions and respecting traditions.



STRUCTURAL DATA

Tile Size	478 x 310 mm
Linear Cover (width)	235 mm
Number of tiles per m ²	10
Batten Centres (mm)*	420 mm
Weight per tile	4.2 kg
Weight per m ²	42.54 kg
Laying Application	Straight Bond
Minimum Roof Pitch	17.5°
Undertile Membrane	Recommended at all pitches Mandatory 17.5° - 25°

* It is advisable to measure approximately 20 tiles on site before battening the roof as tile sizes can vary during the firing of the clay.

HALF-ROUND RIDGE/HIP TILE 50

No. per LM	2.5 tiles
Fixing	47 - 24 cm Bed in mortar/ Dry Ridge System
Laying	Overlapping
Mass	4.3 kg



END HIP TILE 50

No. per LM	Where necessary
Fixing	Bed in mortar/ Dry Ridge System
Laying	Overlapping
Mass	4.2 kg



THREE-WAY JUNCTION

No. per LM	Where necessary
Fixing	Bed in mortar/ Dry Ridge System
Laying	Overlapping
Mass	3.5 kg



RIDGES

These can be fixed using Mortar or the Dry Ridge System. Being quick to lay, the dry ridge provides additional ventilation. It separates the ridge tiles from the roof covering. It prevents any cracking and permits any subsequent replacement of a tile or ridge tile.

HIPS

These can be fixed using Mortar or the Dry Ridge System. MONIER Roofing recommends laying a dry ridge system creating a ventilated sealing solution. This system allows the ridge/hip tile to be separated from the slopes. The tiles alongside the hip are cut to rake.

COLOURS



Silvacane Littoral



Red



Silvacane Xahara

